

XTREAM






Grande efficienza luminosa e un design accattivante lo rendono ideale per l'illuminazione di spazi molto ampi, come capannoni industriali, zone produttive e show-room. Utilizza delle esclusive ottiche da 60°, 90° e 120° in silicone, antiabbagliamento, resistenti ai raggi UV e garantite a vita UL 94.

Great luminous efficiency combined with the fixture captivating design make it ideal to light large areas such as industrial warehouses, and show-rooms.

It is equipped with special 60°, 90°, 120° silicone lenses, anti-glare, UV resistant and lifelong warranty against the yellowing effect UL 94.

Xtream 140 / 180 / 220



Antivandalo IK10
Garanzia a vita UL 94
Resistente ai raggi UV
Antiabbagliamento

Anti-vandal protection optic IK10,
UV Resistant, anti-glare,
no yellowing effect UL 94



Xtreame 140 / 180 / 220

140W / 180W / 220W

CARATTERISTICHE MECCANICHE

Corpo Alluminio + Scocca in Plastica
 Raffreddamento Convezione Naturale – Heat Pipe
 Grado di protezione IP65
 Peso 9 kg

MECHANICAL FEATURES

Body Aluminium + plastic cover
 Cooling system Passive Heat Pipe system
 IP rate IP65
 Peso / Weight 9 kg

CARATTERISTICHE ELETTRICHE

Alimentazione 100-240Vac con PFC
 PFC Attivo > 90
 Potenza Nominale Assorbita 140W (mod. Xtreame 140)
 184W (mod. Xtreame 180)
 220W (mod. Xtreame 220)

ELECTRICAL FEATURES

Input power 100-240Vac with PFC
 PFC Active > 90
 Nominal power absorption 140W (mod. Xtreame 140)
 184W (mod. Xtreame 180)
 220W (mod. Xtreame 220)

CARATTERISTICHE ILLUMINOTECNICHE

Sorgente 1 COB LED
 Tipo di LED CITIZEN
 Efficienza della Sorgente 147 lm/W (mod. Xtreame 140)
 140 lm/W (mod. Xtreame 180)
 136 lm/W (mod. Xtreame 220)
 Temperatura colore 3000K / 4000K / 5000K
 Flusso luminoso della sorgente 20604 lm (mod. Xtreame 140)
 25891 lm (mod. Xtreame 180)
 29995 lm (mod. Xtreame 220)
 CRI 70 / 80 Standard
 Tipo di ottica 60° / 90° / Square 120°
 (Lente in silicone)

LIGHTING FEATURES

Source 1 COB LED
 LED type CITIZEN
 LED Lumen efficiency 147 lm/W (mod. Xtreame 140)
 140 lm/W (mod. Xtreame 180)
 136 lm/W (mod. Xtreame 220)
 Colour temperature 3000K / 4000K / 5000K
 Luminous flux 20604 lm (mod. Xtreame 140)
 25891 lm (mod. Xtreame 180)
 29995 lm (mod. Xtreame 220)
 CRI 70 / 80 Standard
 Lens type 60° / 90° / Square 120°
 (Silicone lens)

**SU RICHIESTA
 UPON REQUEST**

Funzione DIMMING
 DIMMING function

CRI >90

Temperatura colore 2700K o 3500K
 Colour temperature 2700K or 3500K

**DIMENSIONI
 DIMENSIONS**

