



Configuration of the fixture by DRS Setup device.

- Standard fixture colour finishing is grey.

## TECHNICAL FEATURES

### • SOURCE

n. 7 RGBW/FC LEDs  
Total out lumen: R 500lm, G 820lm, B 150lm, W 1050lm

### • OPTIC

8°, 15°, 25°, 40°, 60°, 10°x 30°  
(32mm lenses)

### • TILT

Manual 360°

### • CONTROL

Standard interface: RS-485  
Protocol: USITT DMX 512

### • CONNECTIONS

Signal: XRL 5pin (on request 3pin) male-female connector  
Main Power: 3x1mm cable

### • SETUP AND CONFIGURATION

Remote configuration by DRS Setup device  
Dedicated DMX channel for white balance  
DMX or automatic mode with MASTER/SLAVE function  
Intelligent temperature control  
Flicker free function  
Smooth dimming function  
Halogen simulation  
CYM emulation

### • SAFETY

Safety chain holes

### • IP 67 RATING PROTECTION

### • POWER SUPPLY

Voltage: 100-240VAC

Frequency: 47-63Hz

PFC:

PF>0.91/230VAC, PF>0.98/120VAC

Current: 0.22A@230VAC, 0.38A@120V

Power: 45W

### • DMX CHANNELS

- 9 ch mode

- 5 ch mode

- 4 ch mode

### • PHYSICAL

WxDxH: 185x140x230mm

Weight: 2 Kg.

# Spot Led 7 RGBW FC

