



Spot Led 7 Monochromatic



SPOT LED 7 MONOCHROMATIC IP 67 compact flood projector.

Configuration of the fixture by DRS Setup device or RDM.
This monochromatic version can be used to decorate columns, pillars, walkways, courtyards, steps, to highlight and to enhance details and key elements.

- Colour finishing is grey. No other colours are available.

ITEM	FIXTURE	[KEY features]
LEDs	Monochromatic	7 Hi-power white (warm , neutral , cool)
Total light power		33W
Lumen		4000
Optics		PMMA 8N (38mm lenses) + ultraclear 4mm tempered glass (38 lenses) 8°, 15°, 25°, 40°. 60°, 10°x30°
Tilt		Manual 360°
Safety		Holes for safety chain
Voltage range		100/240VAC, 47-63Hz, Active PFC: >0.98@230V
Power consumption		38W - 0.17A@230V
Control - Setup		Standard interface: RS-485; opto-couplet bi-directional Protocol: USITT DMX 512, RDM Protocol > Integral Wireless DMX control (receiver) is available as an option (art. WI PCB-REC). RDM Control/configuration or individually by DRS (remote control device) Dedicated DMX channel for white balance DMX or Auto mode with Master-Slave function Halogen simulation CYM simulation Flicker-free function Smooth dimming function
Connections		Signal: IN-OUT DMX 4pins IP67 connectors Mains: 3x1 cable (1,5mt)
Operating temperature range		Ta 40°C
Physical		185x140x230 mm
Weight		2 Kg



Spot Led 7 Monochromatic

