

Unik<sup>2</sup>

100/125/150






one<sup>4</sup>all

Led projector for industrial factories  
(indoor and outdoor), large exhibition  
areas and storage facilities.

## PRODUCT FOCUS

- Super compact and extremely performing LED projector
- Vaste range of high efficient silicone lenses
- Excellent light concentration
- Upgradability over the time with the substitution of COB LED and lens
- Low power consumption

## Dimensions



## Mechanical features

<b>BODY</b>	Alluminium
<b>COOLING SYSTEM</b>	Natural convection – Heat Sink
<b>IP RATE</b>	IP65
<b>WEIGHT</b>	3,5 Kg

## Electrical features

<b>INPUT POWER</b>	100-240 Vac con PFC
<b>PFC</b>	Active >90
<b>NOMINAL POWER ABSORPTION</b>	100 W
<b>OPTIONAL DIMMING*</b>	1-10V




\* Upon request other dimming Systems are available

## Lighting features

Source	n°1 COB LED	n°1 COB LED	n°1 COB LED
Colour Temperature*	3000K - CRI 80	4000K - CRI 80	5000°K - CRI 80
Luminous flux	13325 lm (Ta 30°C)	13669 lm (Ta 30°C)	13829 lm (Ta 30°C)
Efficiency (lm/W)	133 lm/W (Ta 30°C)	136 lm/W (Ta 30°C)	138 lm/W (Ta 30°C)
Lens type	15° / 25° / 45° / 60° / 90° / 155° Square120° / Asym1-2-3-4-5	15° / 25° / 45° / 60° / 90° / 155° Square120° / Asym1-2-3-4-5	15° / 25° / 45° / 60° / 90° / 155° Square120° / Asym1-2-3-4-5

\* Upon request other colour temperature (2700K / 3500K) and Higher Chromatic Rendering Index are available (CRI 90)

## Polar image for optics of 60° / 90° / 120°SQ



## Information about the lens:

- Anti-Vandal protection IK10
- Life long warranty against yellowing
- UV Resistant
- Anti-glare

### ONE4ALL S.r.l.




Cascina A valle, 23 | 15038, Ottiglio Monferrato (AL) | ITALY | +39 0142 921338  
www.one4all.it | info@one4all.it



## PRODUCT FOCUS

- Super compact and extremely performing LED projector
- Vaste range of high efficient silicone lenses
- Excellent light concentration
- Upgradability over the time with the substitution of COB LED and lens
- Low power consumption

## Dimensions



## Mechanical features

<b>BODY</b>	Alluminium
<b>COOLING SYSTEM</b>	Natural convection – Heat Sink
<b>IP RATE</b>	IP65
<b>WEIGHT</b>	3,5 Kg

## Electrical features

<b>INPUT POWER</b>	100-240 Vac con PFC
<b>PFC</b>	Active >90
<b>NOMINAL POWER ABSORPTION</b>	123 W
<b>OPTIONAL DIMMING*</b>	1-10V




\* Upon request other dimming Systems are available

## Lighting features

Source	n°1 COB LED	n°1 COB LED	n°1 COB LED
Colour Temperature*	3000K - CRI 80	4000K - CRI 80	5000°K - CRI 80
Luminous flux	15830 lm (Ta 30°C)	16239 lm (Ta 30°C)	16430 lm (Ta 30°C)
Efficiency (lm/W)	129 lm/W (Ta 30°C)	132 lm/W (Ta 30°C)	135 lm/W (Ta 30°C)
Lens type	15° / 25° / 45° / 60° / 90° / 155° Square120° / Asym1-2-3-4-5	15° / 25° / 45° / 60° / 90° / 155° Square120° / Asym1-2-3-4-5	15° / 25° / 45° / 60° / 90° / 155° Square120° / Asym1-2-3-4-5

\* Upon request other colour temperature (2700K / 3500K) and Higher Chromatic Rendering Index are available (CRI 90)

## Polar image for optics of 60° / 90° / 120°SQ



## Information about the lens:

- Anti-Vandal protection IK10
- Life long warranty against yellowing
- UV Resistant
- Anti-glare

### ONE4ALL S.r.l.




Cascina A valle, 23 | 15038, Ottiglio Monferrato (AL) | ITALY | +39 0142 921338  
www.one4all.it | info@one4all.it



## PRODUCT FOCUS

- Super compact and extremely performing LED projector
- Vaste range of high efficient silicone lenses
- Excellent light concentration
- Upgradability over the time with the substitution of COB LED and lens
- Low power consumption

## Dimensions



## Mechanical features

<b>BODY</b>	Alluminium
<b>COOLING SYSTEM</b>	Natural convection – Heat Sink
<b>IP RATE</b>	IP65
<b>WEIGHT</b>	3,5 Kg

## Electrical features

<b>INPUT POWER</b>	100-240 Vac con PFC
<b>PFC</b>	Active >90
<b>NOMINAL POWER ABSORPTION</b>	148 W
<b>OPTIONAL DIMMING*</b>	1-10V




\* Upon request other dimming Systems are available

## Lighting features

Source	n°1 COB LED	n°1 COB LED	n°1 COB LED
<b>Colour Temperature*</b>	3000K - CRI 80	4000K - CRI 80	5000°K - CRI 80
<b>Luminous flux</b>	18170 lm (Ta 30°C)	18640 lm (Ta 30°C)	18860 lm (Ta 30°C)
<b>Efficiency (lm/W)</b>	123 lm/W (Ta 30°C)	126 lm/W (Ta 30°C)	127 lm/W (Ta 30°C)
<b>Lens type</b>	15° / 25° / 45° / 60° / 90° / 155° Square120° / Asym1-2-3-4-5	15° / 25° / 45° / 60° / 90° / 155° Square120° / Asym1-2-3-4-5	15° / 25° / 45° / 60° / 90° / 155° Square120° / Asym1-2-3-4-5

\* Upon request other colour temperature (2700K / 3500K) and Higher Chromatic Rendering Index are available (CRI 90)

## Polar image for optics of 60° / 90° / 120°SQ



## Information about the lens:

- Anti-Vandal protection IK10
- Life long warranty against yellowing
- UV Resistant
- Anti-glare

### ONE4ALL S.r.l.

Cascina A valle, 23 | 15038, Ottiglio Monferrato (AL) | ITALY | +39 0142 921338  
www.one4all.it | info@one4all.it

