

one4all



IP67 Corrosion Free Dimmable T12 LED Tube


Designed for Livestock Farming

—Φ 38mm Double V-Shape 2x150° Beam Angle Vertically Hanging Solution

SPECIFICATION



Product Design



Double V-Shape Design, 2x150° Beam Angle

Double V-Shape Design provides 300° wide beam angle for Vertically Hanging Lighting Solution and uniform lighting distribution.

IP67 Structural Waterproofing

IP67 Structurally waterproof can withstand the high-pressure water cleaning

World-Leading Triac Dimming Technology

Flicker-free smooth Dim-to-0.2% technology provides a perfect simulation of sunrise and sunset for livestock farming application.

More Light, Less Energy

High lighting efficiency, Up to 120-130lm/w

**Over 80000hrs Lifespan,
5 Years Warranty**

Very easy to clean

Fully Round & Smooth Tube Body and lamp cap do not allow any dust and dirt to be stored up, very easy to clean and maintain.

Improve egg /meat production

Different lighting spectrum available to be used for different types of poultry to help egg&meat production.

Patent 360° Aluminum Heat Sink Design

Patent Designed 360° strong aluminum heat sink provides ample cooling to ensure longer lifetime and allows the lamp to run in hot environments

Ammonia & Acid Resistance


Superior outer shell is specially designed to withstand the hard farm environment filled with ammonia and acid.

Product Brief

2V structure design is ONE 4 ALL one more innovation for farm lighting, ONE 4 ALL T12 LED Tube is designed to provide 300° of light coverage in the poultry house, it eliminates shadows or dark areas, the uniform lighting improve animal healthy development. It's made with an optimized color spectrum and full dimming capability to meet chicken's developmental needs, enhance welfare and provide uniform growth. ONE 4 ALL series poultry lights is a retrofit solution for modern poultry systems, acting as an animal welfare friendly alternative to CFL and cold cathode (CCFL) bulbs.

Application

- Chicken farm
- Sheepfold
- Swine Barns
- Cowshed
- Birdcage
- Horse stable and more agricultral
- Refrigerator
- Freezer



Working Conditions




+40°C

~

-20°C

Operating



+60°C

~

-30°C

Storage



10%~85%

Humidity

Dimension





Unit:mm

Model	Dim.A	Dim.B	Dim.C
O4AP2L	600	300	38
O4AP4L	1200	300	38
O4AP5L	1500	300	38
O4AP6L	1800	300	38




Data sheet

Model No.	Dimension (mm)	Power (w)	Luminous Efficiency	CCT	CRI	Viewing Angle	Input Voltage(AC)	Light Source	LED Q'ty (pcs)	Frequency (HZ)
White Color Triac Dimmable 0.2-100% (0-10V Optional)										
O4AP2L-18WTD-W	600	18	120-130lm/w	2700-6500K	>80	2x150°	AC100-120V AC220-240V	SMD2835	192	50/60
O4AP4L-28WTD-W	1200	28							320	
O4AP5L-30WTD-W	1500	30							512	
O4AP6L-30WTD-W	1800	30							576	
Full Spectrum Triac Dimmable 0.2-100% (0-10V Optional)—Designed for Broiler										
O4AP2L-18WTD-F	600	18	100-110lm/w		>80	2x150°	AC100-120V AC220-240V	498nm 625nm	216	50/60
O4AP4L-28WTD-F	1200	28							360	
O4AP5L-30WTD-F	1500	30							576	
O4AP6L-30WTD-F	1800	30							648	
White + Red(2:1) Two Colors Switchable Triac Dimmable 0.2-100% —Designed for Breeder/Layer										
O4AP5L-36WTD-WR	1500	12W Red +24W White	Red:50lm/w White:120lm/w red + white: 100-110lm/w		>80	2x150°	AC100-120V AC220-240V	3000K 625nm	Red188 +White376	50/60
O4AP6L-45WTD-WR	1800	15W Red +30W White							Red208 +White416	

Other length and wattage can be customized.

Installation

A: Hanging Installation



B: Series Connected



Accessories

Parts Name	Picture	Number	Application	Uses Graphic
Hook		1PCS	Hanging Installation	
Top Clamping Plate		1PCS	Fixed to the ceiling when suspending	
Expansion Rubber Plug		3PCS	Embedded ceiling and fixed screws	
Tapping Screw		3PCS	Embedded ceiling and fixed top clamping plate	
Hanging Rope		1PCS	Length adjustable(standard 1m)	