

Unik<sup>2</sup> 60-80 AV






one<sup>4</sup>all

LED GROW LIGHT FOR  
**POULTRY FARMING**

## PRODUCT FOCUS

- High quality Led: CITIZEN, CREE
- Special silicon lenses: they offer an excellent distribution and a perfect light uniformity
- Passive dissipation: Cooling with innovative, small heat-sink e perfect termical features.
- IP 65 projectors

## Dimensions



## Mechanical features

<b>BODY</b>	Aluminum
<b>COOLING SYSTEM</b>	Natural convection -Heat Sink
<b>IP RATE</b>	IP65
<b>WEIGHT (Unik2 60-80 AV)</b>	3 Kg


## Electrical features

<b>INPUT POWER</b>	100-240 Vac with PFC
<b>PFC</b>	Active > 90
<b>NOMINAL POWER ABSORPTION</b>	60 W (UNIK 60 AV)
<b>NOMINAL POWER ABSORPTION</b>	80 W (UNIK2 80 AV)


\* Upon request other dimming Systems are available

## Lighting features

	UNIK2 60 AV	UNIK2 80 AV
<b>SOURCE</b>	n°1 COB LED	n°1 COB LED
<b>COLOUR TEMPERATURE</b>	2700 - 3000 -4000°K	2700 - 3000 -4000°K
<b>LUMINOUS FLUX (4000°K - TA 30°C)</b>	8600 lm	10354 lm
<b>EFFICIENCY (4000°K - TA 30°C)</b>	143 lm/W	141 lm/W
<b>LENS TYPE</b>	60° / 90° / Square 120° / 155° / Asym 1-2-3-4 (All in silicon)	60° / 90° / Square 120° / 155° / Asym 1-2-3-4 (All in silicon)



Photometry:  
155° Optic Square



Photometry:  
155° Optic Square

### Information about products

- Low power absorption and lower heating emission, compared to traditional lamp
- Resistant to chemical agents
- Easy to clean
- Strong, sturdy, which guaranteed durability over time, because it is free from plastic components.

### Information about lens

- Anti-Vandal protection IK10
- Life long warranty against yellowing
- UV Resistant
- Anti-Glare

### On request

- Colour Temperature 3500 - 5000°K
- DIMMING function
- IP68 connectors for wiring



### ONE 4 ALL S.r.l.

Cascina Avalue, 23 | 15038, Ottiglio Monferrato (AL) | ITALY | +39 0142 921338  
www.one4all.it | info@one4all.it

